


Time Locks Equipped With
Standard Movements
Models: 6271, 6291, 6371 and 6391



General Information:

Each movement in the time lock is shock and dust-resistant and is accurate to within one minute every 24 hours. Each movement has a maximum winding time of 144 hours and is designed to operate at temperatures between -5 and $+120$ degrees Fahrenheit.

To Set Time Lock:

1. Determine the amount of time the safe or vault needs to be under time lock protection. Locking time is determined from the time the movements are wound until the time the safe or vault is desired open on the following day. Example:
 - A. Winding time—9:00 a.m.
 - B. Opening time—8:00 a.m. next day
 - C. Lapsed time—23 hours
 - D. Wind each movement to 23 hours.

The movements provided with this time lock can be wound to a maximum of 144 hours. Refer to Time Lock Winding Chart (furnished with each unit) for further guidance, if needed.

2. Insert winding key through holes in front cover directly in front of each time movement. Be sure key is fully inserted before winding.
3. Turn key counter-clockwise until the desired locking time is directly opposite the pointer on the time movement dial. **Caution:** Do not overwind, as movements are not resettable. Repeat this step for each movement in the lock. Each mark on the dial corresponds to one hour while each audible "click" represents 12 minutes.

Note: The first movement to reach "O" will open the lock. The others are for backup purpose only.

4. Visually check each time movement after winding to assure each one is running properly. You will be able to see the components moving. **Never lock the door unless at least two movements are running.** If a movement fails to start after winding, place the winding key on the winding arbor and wiggle the key slightly (but not enough to wind the movement). This causes a motion throughout all wheels of the movement and if the movement starts up readily, no further trouble need be anticipated.
5. Remove winding key after all winding operations are complete.
6. Push the plunger in center of lock case. This plunger should remain in a depressed position. The unit is now in a locked position.

7. Close safe or vault door firmly and lock.

Release Feature:

As a safety feature, this time lock may be changed from a locked position to an unlocked position by pushing the manual release pin to the left and releasing.

Day Open Feature:

As long as the plunger is unpressed, the time lock will remain in the release position after the movements are wound permitting locking and unloading of the safe vault during banking hours.

Important: To use the Day Open Feature, make certain the plunger is in the unlocked (not depressed) position.